Appl. No. 10/774,392

Amendment dated: March 11, 2005 Reply to OA of: September 14, 2004

This listing of claims will replace all prior versions and listings of claims in the application.

## **Listing of Claims**:

1(currently amended). A vehicle tie down rail conjoinment structure comprised of:

[[A]] <u>a</u> first connector having a mounting surface at one extremity and an oblique slip-thrust surface formed at the opposite extremity[[.]]:

[[A]] <u>a</u> second connector having a mounting surface at one extremity and an oblique <u>slip thrust slip-thrust</u> surface formed at the opposite extremity[[.]];

Given the said structure, a threaded fastening component [[is]] utilized to conjoin [[the]] said first connector and [[the]] said second connector into a single physical entity, wherein [[the]] said first connector is inserted into the inner diameter at the end section of a curved anchor footing of a vehicle tie down rail and [[a]] said second coupling section connector is inserted into the inner diameter of a straight, thin long pipe member at the end section of the vehicle tie down rail.

2(currently amended). As mentioned A vehicle tie down rail conjoinment structure as defined in Claim 1 of the vehicle tie down rail conjoinment structure of the invention herein, the wherein said first connector has an annular flange around its outer diameter that partitions it into a first coupling section and the said a second coupling section, wherein [[the]] said first coupling section has a first outer diameter and [[the]] said second coupling section has a second outer diameter.

3(currently amended). As mentioned A vehicle tie down rail conjoinment structure as defined in Claim 2 of the vehicle tie down rail conjoinment structure of the invention herein, the said wherein said first connector further has a mounting surface

Appl. No. 10/774,392

Amendment dated: March 11, 2005 Reply to OA of: September 14, 2004

[[is]] situated at the end surface of [[the]] said first coupling section, and [[the]] said oblique slip thrust surface is situated on [[the]] said second coupling section.

4(canceled).

5(currently amended). As mentioned A vehicle tie down rail conjoinment structure as defined in Claim 3 1 of the vehicle tie down rail conjoinment structure of the invention herein, wherein said second connector has a mounting surface. [[the]] said first connector has a hole in its [[said]] mounting surface and [[the]] said second connector has a threaded hole in its [[said]] mounting surface which thereby enables the conjoinment of [[the]] said two connectors into a single structural entity.